



MOTOR DATA SHEET

MOTOR PART CODE:

0.1843TECAB3

FRAME SIZE:

632-4

50Hz

| | |
|-----------------------|------------|
| Output (kW) | 0.18 |
| Rotation Speed (rpm) | 1310 |
| Voltage | 230/400 |
| Full Load Current (A) | 1.21 0.7 |
| Full Load Torque (Nm) | 1.31221374 |

60Hz

| | |
|-----------------------|------------|
| Output (kW) | 0.216 |
| Rotation Speed (rpm) | 1572 |
| Voltage | 276 480 |
| Full Load Current (A) | 1.21 0.7 |
| Full Load Torque (Nm) | 1.09 |

Efficiency Data

| 100% | 75% | 50% |
|-------------|------------|------------|
| 57 | 56.4 | 52 |

| | |
|--------------------|----------------|
| Factory Reference | MS632-4 |
| Tst/Tn (times) | 2.2 |
| Tmax/Tn | 2.4 |
| Noise (dB) | 52 |
| Moment of inertia | 0.000337967 |
| Type of feet | Removable feet |
| Protection | IP55 |
| Rotation Direction | F / R |
| Cable Glands | 1 - M20× 1.5 |
| Paint Colour | RAL 7024 |
| Efficiency | IE1 |
| Bearing (DE) | 6201 2RZ C3 |

| | |
|---------------------|---------------|
| Power Factor (cos) | 0.65 |
| Tmin/Tn | 2 |
| Ist/In (Times) | 4 |
| Net Weight (Kg) | 4.2 |
| Housing material | Aluminum |
| Insulation Class | F |
| Thermal Protection | PTC 130°C |
| Duty Cycle | S1 |
| Cooling | IC411 |
| Ambient Temperature | -20°C to +40° |
| Bearing Brand | NSK |
| Bearing (NDE) | 6201 2RZ C3 |

Motors designed and manufactured in accordance with:

**IEC 60034
IEC 60038
IEC 60072
2014/30/EU (EMC)
2014/35/EU (LVD)
2011/65/EU (RoHS 2)**

www.tecmotors.co.uk

TEC Electric Motors Ltd. reserves the right to amend or change motor designs or data sheet information