

ODE-3-320153-1042

Optidrive E3 VFD Datasheet

4 kW (5 HP), 15.3 A, 200-240 V, 1-3PH
IP20 Variable Frequency Drive



Input Ratings

Supply Voltage	200-240 V
Input Phases	1
Supply Current Continuous	29.2 A
Supply Fuse or MCB (Type B)	40 A

Output Ratings

Motor Output Rating	4 kW (5 HP)
Output Voltage	0 – Supply Voltage
Output Current	15.3 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC Filter
Brake Transistor	Internal Brake Transistor
Enclosure	IP20
Display	
PCB Coating	

Dimensions

Size	3
Height	261 mm (10.28 in)
Width	131 mm (5.16 in)
Depth	175 mm (6.89 in)
Weight	3.2 kg (7.05 lbs)
Fixings	4 x M5

Packaged Dimensions

Height	254 mm (10 in)
Width	162 mm (6.38 in)
Depth	315 mm (12.4 in)
Weight	3.5 kg (7.72 lbs)



Buy this drive or get more information

Find your local sales partner on
inverterkdrives.com

